


Technical Specification

- | | |
|--|--------------------|
| 1.Connection type | B&S Type J |
| 2.Leakage Distance, | 11 inches (279mm) |
| 3.M&E strength, | 25000 lbs (111kN) |
| 4.Tension proof.kN | 12500 lbs (55.5kN) |
| 5.Impact strength,N-m | 60 inch-lbs (7N-m) |
| 6.Low-frequency dry flashover voltage | 80kV |
| 7.Low-frequency wet flashover voltage | 50kV |
| 8.Critical impulse flashover voltage,positive | 125kV |
| 9.Critical impulse flashover voltage,negative | 130kV |
| 10.Low-frequency puncture voltage | 110kV |
| 11.Radio-influence Voltage: | |
| Low-frequency test voltage | 10kV |
| Maximum RIV at 1,000 kHz | 50 μ V |
| 12.Colour | Grey |
| 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise. | |

6	Split pin	1	Stainless Steel																		
5	Cushion	1	Asphalt																		
4	Cement		Portland																		
3	Pin	1	Forged Steel,Hot Dip Galvanized																		
2	Cap	1	Malleable Cast Iron,Hot Dip Galvanized																		
1	Porcelain	1	High Strength Pcelain																		
Item	Title/Name	Quantity	Note																		
			<table border="1"> <tr> <th colspan="2">Revision details</th> <th>Signature</th> <th>Approved</th> </tr> <tr> <td rowspan="3">Disc Insulator</td> <td>Reference</td> <td colspan="2">52-5-L</td> </tr> <tr> <td>VE No.</td> <td colspan="2">5205LBG1</td> </tr> <tr> <td>Rev</td> <td colspan="2">0</td> </tr> <tr> <td colspan="4">Vanguard Electric,LLC</td> </tr> </table>	Revision details		Signature	Approved	Disc Insulator	Reference	52-5-L		VE No.	5205LBG1		Rev	0		Vanguard Electric,LLC			
Revision details		Signature	Approved																		
Disc Insulator	Reference	52-5-L																			
	VE No.	5205LBG1																			
	Rev	0																			
Vanguard Electric,LLC																					
Weight	12.67 lbs	Page 1 of 1																			