


Technical specification

- | | |
|--|-------------------|
| 1. Minimum creepage distance | 356mm(14 inches) |
| 2. Minimum dry arcing distance | 165mm(6.5 inches) |
| 3. Cantilever breaking load | 12.5kN(2800 lbs) |
| 4. Power frequency dry flashover voltage | 70kV |
| 5. Power frequency wet flashover voltage | 50kV |
| 6. Impulse flashover voltage(Positive) | 120kV |
| 7. Radio interference voltage | |
| Power frequency test voltage to ground | 15kV |
| Maximum RIV at 1,000 kHz | 100µV |
| 8. Colour | Grey |
| 9. All tolerances are according to ANSI C29.1&ANSI C29.7, unless specified otherwise | |

7	Bolt	1	Steel, Hot Deep Galvanized	
6	Cushion	1	Asphalt	
5	Cushion	1	Asphalt	
4	Cement		Portland	
3	Clamp cap	1	Malleable cast iron, hot dip galvanized	
2	Cap	1	Malleable cast iron, hot dip galvanized	
1	Porcelain	1	C120	
Item	Title/Name	Quantity	Note	
		Line Post Insulator	Reference	ANSI 57-11
			VE No.	5711SSG1
			Rev	1
Weight	18 lbs	Page 1 of 1	Vanguard Electric, LLC	