



ITEM	QTY	DESCRIPTION	SPECIFICATION
22	4	Washer 3/8"	Stainless steel
21	3	Spike separator 3/16"	Round brass 5/16"
20	4	Screw back plate	galv screw 3/8X10
19	1	Back plate	Hr 2x3/8 Galv
18	8	Washer 5/16"	Stainless steel
17	8	Washer 5/16"	Stainless steel
16	1	Nameplate	Aluminum 56X41 mm
15	2	Hexagonal Screw 5/16" x 1"	Stainless steel
14	7	Hexagonal screw 5/16" x 3/4"	Stainless steel
13	1	Hook SE	
12	1	Torsion spring	Stainless steel
11	1	Hitch	cu alloy
10	1	Hookstick	Cu alloy
9	2	Contact Sn	Cu electrolytic 3/16X1 3/4
8	3	Lock nut 3/8"	Stainless steel
7	12	Conical washer	Stainless steel
6	3	Screw 3/8X2 1/2"	Stainless steel 304
5	2	Blade	Cu 1 1/4" x 3/16" plating
4	1	Contact input	Cu alloy w/silver plating
3	1	Contact output	Cu alloy w/silver plating
2	2	Insulator	Porcelana Vitrificada
1	1	Base	Galvanized plate HR

NOTE : \* Units in inches



PBL2-27600-00  
600 A  
PORCELAIN INSULATOR

DRAWING :	J. G. C.	15 - OCT - 20
REVISED :	J. C. C.	15 - OCT - 20
APPROVED :	J. G. C.	15 - OCT - 20

PBL2-27600-00  
PBL2 27kV 125kV BIL 600 AMP  
PORCELAIN INSULATOR

Material :	As per specification	Scala :	S/E	Drawing N° :	PBL2-27600-00
------------	----------------------	---------	-----	--------------	---------------